


Part No: 1222LCCH-E00
Description: 1 Pair 22awg Foil Screened + 2core 12awg + 1core 18awg Low Smoke Halogen Free (LSHF).



Units

Data

Conductor Material	: Bare Copper, 22(7)awg
Pair Insulation Material	: Polyethylene (PE)
Number of Pairs	: 1
Drain Wire	: Tinned Copper, 24(7)awg
Overall Screen	: Overall Aluminium Foil (>100% Coverage)
Pair Identification	: White, Violet

Power

Conductor Material	: Bare Copper, 12(7)awg
Core Insulation	: Polyethylene (PE)
Number of Cores	: 2
Core Identification	: Red, Black

Conductor Material	: Bare Copper, 18(7)awg
Core Insulation	: Polyethylene (PE)
Number of Cores	: 1
Core Identification	: Orange

Overall Construction

Sheath Material	: Low Smoke Halogen Free (LSHF)
Sheath Colour	: Blue with White Stripe
Alternative to Lutron	: GRX-CBL-46L GrafikEye

Electrical Characteristics

Nominal Conductor Resistance @ 20°C	: 12awg, <5.8 Ω/km 18awg, <21.5 Ω/km 22awg, <54.0 Ω/km
Insulation Resistance @ 20°C	: > 100 MΩ.M
Capacitance, 22awg	Core to core : 70 pF/m ± 20
	Core to screen : 130 pF/m ± 35
Voltage Rating	: 450/750V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	: 2.5kV for 5 minutes

Physical Characteristics

Overall Diameter	: 8.0 ± 0.2mm
Min Bend Radius	: 10 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 81 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
Low Smoke Generation	: BS EN 61034-2
Halogen Gas Emission	: BS EN 60754-1&2
RoHS Compliant	: Yes
CE Compliant	: LVD (2006/95/EC), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)
UV and Weather Resistant	: ISO 4892-3*
	: *Applies to all Batches ST***** Onwards