


Part Number: 2003PIFPL-E00
Description: 3 x 2 x 20(7)AWG Three Pair Individually Foil Screened LSF Data Cable



Construction

Conductor Material	:	Tinned Copper, 20(7)awg
Insulation Material	:	Polypropylene (PP)
Number of Pairs	:	3
Individual Screen	:	Aluminium Foil, Each Pair (100% Coverage)
Drain Wire	:	Tinned Copper, 22(19)awg
Outer Sheath Material	:	Low Smoke & Fume (LSF)
Outer Sheath Colour	:	Grey
Core Identification	:	Black/Red, Black/White, Black/Green
Alternative to Belden	:	9873

Electrical Characteristics

Nominal Conductor Resistance	:	< 36.8 Ω/km
Insulation Resistance	:	> 200MΩ.M
Capacitance	Core to Core	: 98 pF/m ± 25
	Core to Screen	: 180 pF/m ± 40
Voltage Rating	:	450/750V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	:	2.5kV for 5 minutes

Physical Characteristics

Overall Diameter	:	8.7 ± 0.3mm
Min. Bend Radius	:	10 x OD
Temperature Rating	:	-20°C to +70°C
Weight	:	104 kg/km

Standards

Flame Retardant	:	BS EN 60332-1-2
RoHS3 Compliant	:	Yes
CE Compliant	:	LVD (2014/35/EU), CPR (305/2011)
CPR Classification	:	Eca (EN50575:2014+A1:2016)