


**Description:** 22AWG Multi Pair Individually Foil Screened Data Cable. Low Smoke and Fume Throughout

truSOUND



### Construction

Conductor Material : Tinned Copper, 22(7)awg  
 Insulation Material : Polypropylene (PP)  
 Drain Wire : Tinned Copper, 24(7)awg  
 Individual Screen : Aluminium Foil, Each Pair (100% Coverage)  
 Individual Tape : Polyester, Each Pair  
 Overall Tape : Polyester  
 Outer Sheath Material : Low Smoke and Fume (LSF)  
 Outer Sheath Colour : Grey  
 Core Identification : Colour Chart 3  
 Alternative to Belden : See table

### Electrical Characteristics

Nominal Conductor Resistance : < 53 Ω/km  
 Insulation Resistance : > 200MΩ.M  
 Characteristic Impedance : 50 Ω  
 Capacitance Core to core : 98 pF/m  
                   Core to screen : 180 pF/m  
 Nominal Velocity of Propagation : 66%  
 Voltage Rating : 450/750V *Applies to CE marked FSC branded stock only*  
 Test Voltage : 2.5kV for 5 minutes

### Physical Characteristics

Min. Bend Radius : 10 x OD  
 Temperature Rating : -20°C to +80°C (Fixed)  
 Weight : See table

### Standards

Flame Retardant : IEC 60332-1-2  
 RoHS2 Compliant : Yes  
 CE Compliant : LVD (2006/95/EC)

Part No.	Alternative to Belden	No. of Pairs	O/D (mm)	Weight kg/km
2203PIFRL	8777	3	7.0	70
2206PIFRL	8778	6	9.2	123
2209PIFRL	8774	9	10.6	177
2212PIFRL	9768	12	12.1	226

Tru Cables      Tel: 01727 840 841      info@trucables.com      www.trucables.com

Information and images on this datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.

ISO 9001:2008    Certificate Number: DAS94272226/0/Q

Date: 25/07/2016  
 Revision: 1.0  
 Author: TB      Checked: GB  
 Page Number: 1 of 1