


Part No: 390400
Description: RG 400 50 Ohm Coaxial Cable PTFE Insulation, Double Silver Plated Copper Braid, FEP Brown Sheath



Construction

Conductor Material : Solid Silver Plated Copper Clad Steel
 Conductor Size : 19/0.20mm
 Dielectric : Polytetrafluoroethylene (PTFE)
 Diameter of Dielectric : 2.95 mm
 1st Screen Material : Silver Plated Copper Wire Braid (≥95% Coverage)
 2nd Screen Material : Silver Plated Copper Wire Braid (≥95% Coverage)
 Outer Sheath Material : Fluorinated Ethylene Propylene (FEP)
 Outer Sheath Colour : Brown

Electrical Characteristics

Impedance : 50 Ω ± 3
 Capacitance : 96.5 pF /m ± 5
 Velocity of Propagation : 70 % ± 3
 Max. Conductor Resistance : ≤ 63.3 Ω /km
 Max. Screen Resistance : ≤ 7.5 Ω /km
 Maximum Operating Voltage : 1900V

Attenuation @ 20°C

Frequency (MHz)	Attenuation (dB/100m)	Frequency (MHz)	Attenuation (dB/100m)
10	3.6	900	40.4
50	8.5	1000	43.0
100	12.5	2000	63.3
200	17.7	3000	79.4
400	25.9	5000	107.0
700	35.1	8000	141.7

Physical Characteristics

Overall Diameter : 5.0 mm (±0.15mm)
 Min. Bend Radius : 10 x OD
 Temperature Rating : -55°C to +200°C
 Weight : 55 kg/km

Standards

RoHS3 Compliant : Yes