

Part No: C5EFHR-E00
Description: The TruLan Cat 5E F/UTP cable is the ideal choice for high speed data networks across a home or building.




TESTED TO
350MHz

Construction

Conductor : Bare Copper
AWG : 24(1)
Insulation Material : High Density Polyethylene (HDPE)
Number of Pairs : 4
Pair Identification : White/Blue, Blue/White; White/Orange, Orange/White
 : White/Green, Green/White; White/Brown, Brown/White
Drain Wire : 24(1)AWG, Tinned Copper
Overall Screen : Aluminium Foil (100% Coverage)
Sheath Material : Low Smoke Halogen Free (LSHF)
Sheath Colour : Orange



Electrical Characteristics

Max. Conductor Resistance @ 20°C : ≤ 9.5 Ω/100m
Max. Resistance Unbalanced : ≤ 2.5 %
Nominal Impedance (1-100MHz) : 100 ± 15 Ω
Mutual Capacitance : ≤ 5.6nF/100m
Capacitance Unbalanced to Earth : ≤ 330 pF/ 100m
NVP : 68.5 %
Max. Delay Skew : ≤ 45 nS/ 100m
Voltage Rating EN 50525-1 : 450/750V*
Test Voltage : 2.5kV (AC)

*Suitable for installation where Band II 450/750v cables are present. Not suitable for connection to mains supply

Physical Characteristics

Overall Diameter : 6.2 ± 0.3mm
Bend Radius : Fixed 4 x OD Flexing 8 x OD
Temperature Rating : Fixed -20°C to 60°C Flexing -10°C to 60°C
Weight : 42 kg/km

Transmission Performance

| Frequency | 1 | 4 | 10 | 16 | 20 | 31.25 | 62.5 | 100 | 155 | 200 | 300 | 350 | MHz |
|-------------|------|------|------|------|------|-------|------|------|------|------|------|------|------|
| Attenuation | 2.1 | 3.90 | 6.2 | 7.90 | 8.9 | 11.2 | 16.2 | 21.0 | 26.6 | 30.7 | 38.7 | 41.4 | ≤ dB |
| Return Loss | 19.0 | 19.0 | 19.0 | 19.0 | 19.0 | 17.1 | 14.1 | 12.0 | 10.1 | 9.0 | 7.2 | 6.6 | ≥ dB |
| NEXT | 60.0 | 54.8 | 48.5 | 45.2 | 43.7 | 40.5 | 35.7 | 32.3 | 29.2 | 27.3 | 24.4 | 23.2 | ≥ dB |
| PS NEXT | 57.0 | 51.8 | 45.5 | 42.2 | 40.7 | 37.5 | 32.7 | 29.3 | 27.0 | 25.2 | 22.3 | 21.2 | ≥ dB |
| ACRF | 58.6 | 46.6 | 38.6 | 34.5 | 32.6 | 28.7 | 22.7 | 18.6 | 17.5 | 15.3 | 11.8 | 10.5 | ≥ dB |
| PSACRF | 55.6 | 43.6 | 35.6 | 31.5 | 29.6 | 25.7 | 19.7 | 15.6 | 11.8 | 9.6 | 6.1 | 4.7 | ≥ dB |

Standards

| | |
|--|--|
| Flame Retardant : BS EN 60332-1-2 | Low Smoke Generation Approval : BS EN 61034-2 |
| Halogen Gas Emission : BS EN 60754-1&2 | UN Regulation No. 118 Annex 10 : UN Regulation No. 118 Annex 10 |
| RoHS3 Compliance : Yes | Manufactured in accordance to : TIA/EIA 568-C.2, ISO/IEC 11801 |
| CE Compliant : LVD (2014/35/EU), CPR (305/2011) | CPR Classification : Eca (EN50575:2014+A1:2016) |

FS Cables
 Shoal Export

01727 840 841
 +44 1727 849 841

sales@fscables.com
 sales@shoal-export.com

www.fscables.com
 www.shoal-export.com

Part Number: C5EHR-E00
Date: 29/10/2021
Revision: 1.4
Author: SK Checked: SK
Page Number: 1 of 1

Information and images on this technical datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.