


E14a: UC^{FIBRE™} Universal Central Tube Cable

2000N central tube cable with 2-24 fibres, glass elements and FireBur® sheath, VDE U-DQ(ZN)BH



Application and installation

This cable can be used for LAN and WAN backbones, telecom access lines, fibre to business and fibre to the building drop connections as well as fibre to the home drop and access connections.

With its FireBur® LSHF sheathing this cable is ideal for mixed indoor and outdoor installation. It is equally suited for installation in ducts and on trays. It has a degree of rodent protection.

Standards

ISO 11801-1, EN 50173-1:2011, IEC 60794-1

Flame Resistance

LSHF (LSOH): IEC 60332-1-2, IEC 60754-1, IEC 60754-2, IEC 61034-2; Class Eca

Construction

Loose tube	Ø2.8 mm gel-filled loose tube with 2 – 24 fibres		
Fibre colour code	1	Red	13 Red w/mark every 70mm
	2	Green	14 Green w/mark every 70mm
	3	Blue	15 Blue w/mark every 70mm
	4	Yellow	16 Yellow w/mark every 70mm
	5	White	17 White w/mark every 70mm
	6	Grey	18 Grey w/mark every 70mm
	7	Brown	19 Brown w/mark every 70mm
	8	Violet	20 Violet w/mark every 70mm
	9	Turquoise	21 Turquoise w/mark every 70mm
	10	Black	22 White w/mark every 35mm
	11	Orange	23 Orange w/mark every 70mm
	12	Pink	24 Pink w/mark every 70mm
Strength member	Water-blocked E-Glass fibre elements		
Sheath	1.0 mm Blue (Black optional) FireBur® sheath, UV stabilised, IEC 50290-2-27		
Sheath marking	Draka UC ^{FIBRE} I/O CT LSHF 2.0 kN <Fibre count> <Fibre type><Fibre brand><Item No><Factory code><Batch Number><Meter mark> U-DQ(ZN)BH <Fibre count> <Fibre family> <Mode field diameter> /125 <Transmission Class>		

E14a: UC^{FIBRE}™ Universal Central Tube Cable

Physical Properties

Attribute	IEC 60794-1-21/22 Method	Limits
Nominal outer diameter	-	2 - 24 fibres: 5,8 mm
Nominal weight	-	2 - 24 fibres: 40 kg/km
Maximum installation tensile strength	E1	2000 N (fibre strain ≤ 0,6%)
Permanent tensile strength	E1	750 N (fibre strain ≤ 0,2%)
Compressive strength (crush)	E3	2000 N / 100 mm
Impact	E4	15 Nm (no attenuation change, no broken cable elements)
Torsion	E7	5 cycles ± 1 turn
Kink	E10	The cables do not form a kink when a loop is drawn together to a diameter of 100 mm
Min. bending radius, unloaded (permanent)	E11	R = 58 mm
Min. bending radius, loaded (installation)	-	R = 116 mm
Temperature range	F1	Storage: -40°C to +60°C Installation: -30°C to +40°C Operation: -30°C to +60°C.
Water penetration	F5B	No water on free end
Heat of combustion	-	2-24 fibres: 630 MJ/km = 0,18 kWh/m

Product Codes

Product Code	DoP Number*	Product Description	Fibre Count	Fibre Type	Fibre Data Sheet
60043938	1002435	UC ^{FIBRE} I/O CT LSHF 2kn 2 OM2B	2	MaxCap-BB-OM2	C34
60018814	1002406	UC ^{FIBRE} I/O CT LSHF 2kn 4 OM2B	4	MaxCap-BB-OM2	C34
60018815	1002407	UC ^{FIBRE} I/O CT LSHF 2kn 6 OM2B	6	MaxCap-BB-OM2	C34
60018780	1002401	UC ^{FIBRE} I/O CT LSHF 2kn 8 OM2B	8	MaxCap-BB-OM2	C34
60011400	1002397	UC ^{FIBRE} I/O CT LSHF 2kn 12 OM2B	12	MaxCap-BB-OM2	C34
60073246	1008123	UC ^{FIBRE} I/O CT LSHF 2kn 24 OM2B	24	MaxCap-BB-OM2	C34
60019958	1002415	UC ^{FIBRE} I/O CT LSHF 2kn 4 OM2B BK	4	MaxCap-BB-OM2	C34
60019959	1007110	UC ^{FIBRE} I/O CT LSHF 2kn 8 OM2B BK	8	MaxCap-BB-OM2	C34
60029781	1002397	UC ^{FIBRE} I/O CT LSHF 2kn 12 OM2B BK	12	MaxCap-BB-OM2	C34
60073317	1008126	UC ^{FIBRE} I/O CT LSHF 2kn 24 OM2B BK	24	MaxCap-BB-OM2	C34
60018863		UC ^{FIBRE} I/O CT LSHF 2kn 4 OM3B	4	MaxCap-BB-OM3	C31
60011320		UC ^{FIBRE} I/O CT LSHF 2kn 6 OM3B	6	MaxCap-BB-OM3	C31
60018784	1002402	UC ^{FIBRE} I/O CT LSHF 2kn 8 OM3B	8	MaxCap-BB-OM3	C31
60018785	1002403	UC ^{FIBRE} I/O CT LSHF 2kn 12 OM3B	12	MaxCap-BB-OM3	C31
60019389		UC ^{FIBRE} I/O CT LSHF 2kn 16 OM3B	16	MaxCap-BB-OM3	C31
60073248	1008125	UC ^{FIBRE} I/O CT LSHF 2kn 24 OM3B	24	MaxCap-BB-OM3	C31
60019960	1002416	UC ^{FIBRE} I/O CT LSHF 2kn 4 OM3B BK	4	MaxCap-BB-OM3	C31
60019961	1004779	UC ^{FIBRE} I/O CT LSHF 2kn 8 OM3B BK	8	MaxCap-BB-OM3	C31
60019962	1002418	UC ^{FIBRE} I/O CT LSHF 2kn 12 OM3B BK	12	MaxCap-BB-OM3	C31
60073155	1008272	UC ^{FIBRE} I/O CT LSHF 2kn 24 OM3B BK	24	MaxCap-BB-OM3	C31
60019938	1002414	UC ^{FIBRE} I/O CT LSHF 2kn 4 OM4B	4	MaxCap-BB-OM4	C32
60020010	1002420	UC ^{FIBRE} I/O CT LSHF 2kn 6 OM4B	6	MaxCap-BB-OM4	C32
60020747		UC ^{FIBRE} I/O CT LSHF 2kn 8 OM4B	8	MaxCap-BB-OM4	C32

E14a: UC^{FIBRE}™ Universal Central Tube Cable

60019481	1002411	UC ^{FIBRE} I/O CT LSHF 2kN 12 OM4B	12	MaxCap-BB-OM4	C32
60073244	1008122	UC ^{FIBRE} I/O CT LSHF 2kN 24 OM4B	24	MaxCap-BB-OM4	C32
60032535	1002428	UC ^{FIBRE} I/O CT LSHF 2kN 4 OM4B BK	4	MaxCap-BB-OM4	C32
60020747	1002422	UC ^{FIBRE} I/O CT LSHF 2kN 8 OM4B BK	8	MaxCap-BB-OM4	C32
60029958	1005428	UC ^{FIBRE} I/O CT LSHF 2kN 12 OM4B BK	12	MaxCap-BB-OM4	C32
60032388	1004361	UC ^{FIBRE} I/O CT LSHF 2kN 16 OM4B BK	16	MaxCap-BB-OM4	C32
60073165	1008170	UC ^{FIBRE} I/O CT LSHF 2kN 24 OM4B BK	24	MaxCap-BB-OM4	C32
		UC ^{FIBRE} I/O CT LSHF 2kN 4 OM5B	4	WideCap-OM5	C39
		UC ^{FIBRE} I/O CT LSHF 2kN 8 OM5B	8	WideCap-OM5	C39
		UC ^{FIBRE} I/O CT LSHF 2kN 12 OM5B	12	WideCap-OM5	C39
		UC ^{FIBRE} I/O CT LSHF 2kN 16 OM5B	16	WideCap-OM5	C39
		UC ^{FIBRE} I/O CT LSHF 2kN 24 OM5B	24	WideCap-OM5	C39
60019305		UC ^{FIBRE} I/O CT LSHF 2kN 2 SM2D	2	OS2 G652.D	C03e
60011327	1004732	UC ^{FIBRE} I/O CT LSHF 2kN 4 SM2D	4	OS2 G652.D	C03e
60011330	1002394	UC ^{FIBRE} I/O CT LSHF 2kN 6 SM2D	6	OS2 G652.D	C03e
60011304	1002390	UC ^{FIBRE} I/O CT LSHF 2kN 8 SM2D	8	OS2 G652.D	C03e
60024865	1004785	UC ^{FIBRE} I/O CT LSHF 2kN 12 SM2D	12	OS2 G652.D	C03e
60011335	1002398	UC ^{FIBRE} I/O CT LSHF 2kN 16 SM2D	16	OS2 G652.D	C03e
60073062		UC ^{FIBRE} I/O CT LSHF 2kN 24 SM2D	24	OS2 G652.D	C03e
60058208	1004812	UC ^{FIBRE} I/O CT LSHF 2kN 2 SM2D BK	2	OS2 G652.D	C03e
60027528	1002425	UC ^{FIBRE} I/O CT LSHF 2kN 4 SM2D BK	4	OS2 G652.D	C03e
60026545	1002424	UC ^{FIBRE} I/O CT LSHF 2kN 8 SM2D BK	8	OS2 G652.D	C03e
60011334	1002434	UC ^{FIBRE} I/O CT LSHF 2kN 12 SM2D BK	12	OS2 G652.D	C03e
60028301	1003030	UC ^{FIBRE} I/O CT LSHF 2kN 16 SM2D BK	16	OS2 G652.D	C03e
60073166	1008171	UC ^{FIBRE} I/O CT LSHF 2kN 24 SM2D BK	24	OS2 G652.D	C03e
60033658		UC ^{FIBRE} I/O CT LSHF 2kN 4 SM7A1	4	BendBright G.657.A1	C17
60033659	1002429	UC ^{FIBRE} I/O CT LSHF 2kN 8 SM7A1	8	BendBright G.657.A1	C17
60037350	1004796	UC ^{FIBRE} I/O CT LSHF 2kN 12 SM7A1	12	BendBright G.657.A1	C17
60073325	1008211	UC ^{FIBRE} I/O CT LSHF 2kN 24 SM7A1	24	BendBright G.657.A1	C17
60066411		UC ^{FIBRE} I/O CT LSHF 2kN 12 SM7A1 BK	12	BendBright G.657.A1	C17
60019522	1004769	UC ^{FIBRE} I/O CT LSHF 2kN 4 SM7B	4	BendBright ^{XS} G.657.A2	C24
60020265		UC ^{FIBRE} I/O CT LSHF 2kN 6 SM7B	6	BendBright ^{XS} G.657.A2	C24
60060409	1004830	UC ^{FIBRE} I/O CT LSHF 2kN 12 SM7B	12	BendBright ^{XS} G.657.A2	C24
60073264		UC ^{FIBRE} I/O CT LSHF 2kN 24 SM7B	24	BendBright ^{XS} G.657.A2	C24
60020751		UC ^{FIBRE} I/O CT LSHF 2kN 16 SM2D/OM3B	16	Hybrid 8 OS2 single mode + 8 MaxCap-BB-OM3	C03 C31
		UC ^{FIBRE} I/O CT LSHF 2kN 24 SM2D/OM3B	24	Hybrid 12 OS2 single mode + 12 MaxCap-BB-OM3	C03 C31

*DoP Numbers are per product code and any DoP number proves CPR approval for the cable. DoP files can be downloaded from the website: www.prysmiangroup.com/cpr

© PRYSMIAN GROUP 2016, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

C02: General purpose 62.5 µm fibre

Properties of cabled OM1 fibre for use at 850 nm and at 1300 nm

General and application

This fibre is a graded-index multimode fibre suitable for transmission speeds of up to 10 Gbps (33m 10GBASE-SR). It has 62.5 µm core and 125 µm cladding diameter. The fibre is designed for use at 850 and 1300 nm.

This fibre is suitable for use in premises wiring application like LAN's with video, data and or voice services using LED, VCSEL and Fabry-Perot laser sources.

Standards

IEC 60793-2-10 Category A1b	ISO/IEC 11801 category OM1
EN 60793-2-10: type A1b	IEEE 802.3 - 2002 with amendment 802.3ae - 2002
TIA/EIA-492 AAAA	ANSI/TIA/EIA-568.B.3 - 2000
EN 50173-1:2007 category OM1	IBM™ Fibre Optic Channel Links; ESCON™

Cabled Fibre Attenuation

Attribute	Measurement method	Units	Limits
Attenuation limit according to IEC 60793-2-10, 850 nm	IEC 60793-1-40	dB/km	≤ 3.5
Attenuation limit according to IEC 60793-2-10, 1300 nm	IEC 60793-1-40	dB/km	≤ 1.5

Optical Specifications (Bare Fibre)

Attribute	Measurement method	Units	Limits
Attenuation at 850 nm	IEC 60793-1-40	dB/km	≤ 2.9
Attenuation at 1300 nm	IEC 60793-1-40	dB/km	≤ 0.6
Point Discontinuity at 850 nm and 1300 nm	IEC 60793-1-40	dB	≤ 0.1

Bending Loss

Mandrel Radius = 37.5 mm, 100 turns at 850/1300 nm	IEC 60793-1-40	dB	≤ 0.5
--	----------------	----	-------

Bandwidth

Overfilled (OFL) modal bandwidth at 850 nm	IEC 60793-1-41	MHz • km	≥ 200
Overfilled (OFL) modal bandwidth at 1300 nm	IEC 60793-1-41	MHz • km	≥ 600

C02: General purpose 62.5 µm fibre

Geometrical properties

Attribute	Measurement method	Units	Limits
Core diameter	IEC 60793-1-20	µm	62.5 ± 2.5
Cladding diameter	IEC 60793-1-20	µm	125.0 ± 1.0
Cladding non-circularity	IEC 60793-1-20	%	≤ 1.0
Core non-circularity	IEC 60793-1-20	%	≤ 5
Core-cladding concentricity error	IEC 60793-1-20	µm	≤ 1.5
Primary coating diameter – uncoloured	IEC 60793-1-21	µm	242 ± 7
Primary coating diameter - coloured	IEC 60793-1-21	µm	250 ± 15
Primary coating non-circularity	IEC 60793-1-21	%	≤ 6
Primary coating-cladding concentricity error	IEC 60793-1-21	µm	≤ 10

Mechanical properties

Attribute	Measurement method	Units	Limits
Proof stress level	IEC 60793-1-30	GPa	≥ 0.7 (≈ 1 %)
Typical average strip force	IEC 60793-1-32	N	≥ 1.3 ≤ 3.0
Peak strip force	IEC 60793-1-32	N	≥ 1.3 ≤ 8.9

Group index of refraction

Attribute	Measurement method	Units	Limits
Group index of refraction at 850 nm	IEC 60793-1-22	-	1.496
Group index of refraction at 1300 nm	IEC 60793-1-22	-	1.491

© PRYSMIAN GROUP 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.