LiYCY Multicore Braid Screened Colour Coded PVC
Technical Datasheet

Description: Multicore Signal & Control Cable with Tinned Copper Wire Braid, Polyvinyl Chloride (PVC) Grey Sheath.



Construction

Conductor Material	: Bare Copper, Class 5
Insulation Material	: Polyvinyl Chloride (PVC)
Overall Screen	: Tinned Copper Wire Braid (≥ 70% Coverage)
Sheath Material	: Polyvinyl Chloride (PVC)
Sheath Colour	: Grey
Core Identification	: 2core – Brown, Blue 3core – Brown, Blue, Green/Yellow
	: 4core – Brown, Black, Grey, Green/Yellow
	: 5core – Brown, Black, Grey, Blue, Green/Yellow

Electrical Characteristics

Conductor Resistance	: BS EN 60228
Insulation Resistance	: 200 MΩ.M
Working Voltage	: 300/500V
Test Voltage (AC)	: 2000V

Physical Characteristics

Bend Radius	: Flexing 15 x OD Static 10 x OD
Temperature Rating	: Flexing -5°C to +70°C Static -20°C to +70°C

Standards

Flame Retardant	: BS EN 60332-1-2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU)

Part No.	Cores x mm²	Weight kg/km	OD mm
32000702C	2 x 0.75	56	5.9
32000703C	3 x 0.75	70	6.2
32000704E	4 x 0.75	95	6.7
32000705E	5 x 0.75	130	7.5
32001002C	2 x 1.0	84	6.2
32001003C	3 x 1.0	110	6.5
32001004E	4 x 1.0	130	7.2
32001005E	5 x 1.0	156	8.1

Part No.	Cores x mm²	Weight kg/km	OD mm
32001502C	2 x 1.5	97	7.5
32001503C	3 x 1.5	125	7.9
32001504E	4 x 1.5	165	8.8
32001505E	5 x 1.5	193	9.1
32002502C	2 x 2.5	148	8.6
32002503C	3 x 2.5	188	9.1
32002504E	4 x 2.5	236	9.9
32002505E	5 x 2.5	270	11.0

Part No.	Cores x mm²	Weight kg/km	OD mm
32004003C	3 x 4.0	250	10.4
32004004E	4 x 4.0	302	11.6
32004005E	5 x 4.0	370	12.9
32006003C	3 x 6.0	285	13.1
32006004E	4 x 6.0	412	14.2
32006005E	5 x 6.0	505	15.5
32010004E	4 x 10	620	17.5
32010005E	5 x 10	796	19.7
32016004E	4 x 16	1090	20.5
32016005E	5 x 16	2070	22.4

FS Cables
Shoal Export
01727 840 841
+44 1727 849 841
sales@fscables.com
sales@shoal-export.com
www.fscables.com
www.shoal-export.com

Date: 08/09/2020
Revision: 1.0
Author: GB Checked: GB

Information and images on this techincal datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.