



# RG 213 U Marine ARM

50Ω

Flexible, SHF1

DNV-GL, ABS



sales@fscables.com


## Application

Armoured coaxial cable for ship- and offshore applications. VHF/UHF equipment. Electrical specifications in compliance with MIL C-17/F. The steel braid meets EU EMC requirements. Identical to RG 215 U.



## Construction

Conductor	Stranded Plain Cu 7 x 0.75 [mm]
Dielectricum	Low density PE 7.25 ± 0.18 [mm]
Screen	Al + polyester + Al tape 100 [% optical coverage]
Screen 2	Cu- braid 96 [% optical coverage]
Inner jacket	SHF1
Armour alt.1	Galvanised steel wire braid 144 x 0.24 mm
Armour alt.2	Tinned Cu-braid 144 x 0.24 mm
Armour alt.3	Bronze wire braid 144 x 0.24 mm
Jacket	Black SHF1
O.D.	13.50 ± 0.20 [mm]
Weight	295 [kg/km]



## Specifications

Operating temperature	-40 – +70 [°C]
Characteristic impedance	50 ± 2 Ω
Braid Resistance	4.4 [Ω/km]
Conductor resistance	8 [Ω/km]
Test voltage	5.5 [kV]
Capacitance	100 [pF/m]
Velocity factor	0.66
Min. bending radius	5
Min. bending radius flexible	10

## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1, 2
Design and testing standards	IEC 60096-0-1 Ed 3 IEC 61196-1-100
Sheathing material	IEC 60092-360 (359) NEK 606
Flame retardant	IEC 60332-1
Fire retardant	IEC 60332-3-22 Cat.A
Smoke emission	IEC 61034-1, -2
Certification	DNV-GL, ABS
Part No.	1092441 (GSWB)



This product is available with MUD resistant jacket.

## Attenuation nominal, max 105%

Frequency MHz	Attenuation dB/100m
5	1.1
10	1.5
50	3.8
100	5.5
200	8
300	10.1
500	13.2
800	17.5
1000	20
1500	25.3
2150	31.5
2500	34.7
2750	36.7
3000	38.3

## Structural return loss

MHz	dB
30 – 300	>31
300 – 600	>28
600 – 1000	>20
1000 – 2000	>24
2000 – 3000	>22



## Screen effectiveness IEC 61196-1

MHz	dB
100 – 900	>90
900 – 2000	>80
2000 – 3000	>70