

Profinet B, Industrial BUS

100 Ω BUS-cable
2 pair Quad, 0,35 mm²
SHF1, UV
DNV-GL

FS
cables

sales@fscables.com

Application


Double screened. Data transmission in industrial environments as well as in ship- offshore installations. Designed for EMC installations. Flexible cable with SHF1 jacket.

Construction

Conductor	0.35 [mm ²] Stranded tinned Cu AWG 22/7
Insulation	PE, Ø=1,55 ± 0,05 [mm] 2 pairs quad
Colour code	White, blue, yellow, orange
Filler	Optional
Inner jacket	LSZH
Screen	Al/Mylar 100 [%cover]
Screen 2	Tinned Cu-braid ≥85 [%cover]
Outer Jacket	Green SHF1
O.D.	6,5 [mm]

Jacket marking

NEK Kabel - Profinet B MARIN Cable 4x22AWG SHF1 - DNV-GL - 60332-3-22 - batch no - DD/MM/YY - ****m




Specifications

Operating temperature	-40 - +80 [°C]
Temperature @ installation	-20 + 60 [°C]
Dielectric strength	DC 1,5kV for 1min.
Characteristic impedance	100 ± 15 Ω at 1 - 100MHz
Conductor resistance	≤59,4 [Ω/km]



Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1, 2
Material properties, insulation and sheath	IEC 60092-360 3582
Design and testing standards	IEC 61158-2 TIA/EIA 568 C.2
Flame resistance	IEC 60332-3-22 Cat.A
Flame retardant	IEC 60332-1-2
Oil and fuel, hydrocarbons resistant	IEC 60811-2-1 IRM 902 23°C / 7 days, 70°C / 4h
Smoke emission	IEC 61034-2 , ≥60%
UV-resistant	UL 1581 (300H)
Certification	DNV-GL



Part No.	1091069
----------	---------

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)
1	2,4	65,3
4	4,9	56,3
8	5,8	51,8
10	7,0	50,3
16	9,8	47,2
20	11,2	45,8
25	12,5	44,3
31,25	14,0	42,9
62,5	20,4	38,4
100	26,4	35,3

Updated

Date	Rev.	Description
05.04.2019	1	DNV-GL Approved
15.04.2019	2	Additional information
09.01.2020	3	Jacket marking