

Part Number: TSM03040
Description: TruSound 0.34mm² 4 core flexible microphone cable in black PVC




Construction

Conductor Material	: Oxygen Free Bare Copper
Number of Strands	: 42/0.1mm
Insulation Material	: High Density Polyethylene (HDPE)
Number of Cores	: 4
Fillers	: Cotton
Tape	: Overall Fleece
Overall Screen	: Tinned Copper Wire Braid (90% Coverage)
Outer Sheath Material	: Polyvinyl Chloride (PVC)
Outer Sheath Colour	: Black
Core Identification	: White/Blue, White/Blue

Electrical Characteristics

Nominal Conductor Resistance	: < 57.50 Ω/km
Insulation Resistance	: > 200MΩ.M
Capacitance	Core to Core : 76 pF/m ± 25
	Core to Screen : 152 pF/m ± 35
Voltage Rating	: 450/750V <i>Applies to CE marked FSC/Tru branded stock only</i>
Test Voltage	: 2.5kV for 1 minute

Physical Characteristics

Overall Diameter	: 6.0 ± 0.2mm
Min. Bend Radius	: 15 x OD
Temperature Rating	: -40°C to +80°C
Weight	: 64 kg/km

Standards

RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU)