


**Part No.:** TSS162C-F00  
**Description:** TruSound 16awg two core speaker cable with a PE outer sheath and a water blocking tape. The cable also has oxygen free bare copper conductors.

### Construction

Conductor Material : 99.999% Oxygen Free Bare Copper  
 Number of Strands : 41/0.2mm  
 Insulation Material : Polyvinylchloride (PVC)  
 Number of Cores : 2  
 Overall Tape : Water Blocking Fleece  
 Sheath Material : Polyethylene (PE)  
 Sheath Colour : Black  
 Core Identification : Red, Black



### Electrical Characteristics

Nominal Conductor Resistance : < 13.7 Ω/km  
 Insulation Resistance : > 200 MΩ.M  
 Voltage Rating : 450/750V *Applies to CE marked FSC/Tru branded stock only*  
 Test Voltage : 2.5kV for 5 Minutes

### Physical Characteristics

Overall Diameter : 6.5 ± 0.2mm  
 Min. Bend Radius : 10 x OD  
 Temperature Rating : 0°C to +70°C  
 Weight : 40 kg/km

### Standards

RoHS3 Compliant : Yes  
 UV & Weather Resistant : ISO 4892-3  
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)  
 CPR Classification : Fca (EN50575:2014+A1:2016)