



DESCRIPTION:

A comprehensive range of single fixing cable cleats to provide a simple, but strong means of securing cables. Suitable for use with cables or pipes up to 50.8mm in diameter. Available in 12 different sizes in standard Polypropylene material or in a halogen-free material.

SPECIFICATION:

MATERIAL: Polypropylene/LSF Zero Halogen Polypropylene

RESISTANCE: High level of UV resistance.

SERVICE TEMPERATURE RANGE: -35°C to +105°C



PART NUMBERS:

PART NO. STANDARD	PART NO. LSF	CLEAT SIZE	STUD HOLE SIZE	CABLE RANGE MIN. (mm)	CABLE RANGE MAX. (mm)	PACK QTY
CC5	CC5LSF	5	M6	10.1	12.7	1
CC6	CC6LSF	6	M6	12.6	15.2	1
CC7	CC7LSF	7	M6	15.1	17.8	1
CC8	CC8LSF	8	M6	17.7	20.3	1
CC9	CC9LSF	9	M6	20.2	22.8	1
CC10	CC10LSF	10	M6	22.7	25.4	1
CC11	CC11LSF	11	M10	25.3	27.7	1
CC12	CC12LSF	12	M10	27.6	30.5	1
CC14	CC14LSF	14	M10	30.4	35.5	1
CC16	CC16LSF	16	M10	35.4	40.6	1
CC18	CC18LSF	18	M10	40.5	45.7	1
CC20	CC20LSF	20	M10	45.6	50.8	1

SELECTION GUIDE							
FOR SWA CABLES - CABLE SIZE mm ²							
CABLE CORES	1.5	2.5	4.0	6.0	10	16	25
2 CORES	CC5	CC6	CC7	CC7	CC8	CC9	CC12
3 CORES	CC5	CC6	CC8	CC8	CC9	CC10	CC12
4 CORES	CC6	CC6	CC8	CC8	CC9	CC11	CC12
CABLE CORES	35	50	70	95	120	150	185
2 CORES	CC12	CC11	CC12	CC14	CC16	CC18	CC20
3 CORES	CC12	CC12	CC14	CC16	CC18	CC20	-
4 CORES	CC14	CC14	CC16	CC18	CC20	-	-



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297