



Our range of stainless steel coated cable ties are coated with polyester and epoxy. They are manufactured from 316 stainless steel and have a high tensile strength. The self-locking head design speeds installation and locks into place at any length along the tie. The fully enclosed head does not allow dirt or grit to interfere with the locking mechanism. These ties are flame retardant, tough and corrosion resistant and are ideal for demanding industries such as mass transit, ship building, oil rigs, and mining.

SPECIFICATION:

COLOUR OPTIONS: Black as Standard. Red, Blue, Green or Yellow available MOQ apply.

MATERIAL: 316 Stainless Steel

COATING: Pure Polyester/Epoxy

OPERATING TEMPERATURE: -80°C to +150°C

FLAMMABILITY: Fireproof, Halogen-Free, UV Resistant

STANDARDS: DNV CERT. NO. E-6729.

LOOP TENSILE STRENGTH: 4.6mm width: 667N (150lb)
7.9mm width: 1335N (300lb)
12.7mm width: 3115N (700lb)

CHEMICAL RESISTANCE: Salt spray resistant, corrosion resistant, weather resistant, outstanding chemical resistance, antimagnetic.



PART NUMBERS:

PART NO.	WIDTH (mm)	LENGTH (mm)	MAX. BUNDLE DIA. (mm)	MIN. TENSILE STRENGTH Kg	PACK QTY
CTR200STC	4.6	200	50	45	100
CTR200STC-RED		200	50	45	100
CTR300STC		300	76	45	100
CTR300STC-RED		300	76	45	100
CTR360STC		360	102	45	100
CTR520STC		520	152	45	100
CTR680STC		680	200	54	100
CTR200HDSTC	7.9	200	50	54	100
CTR300HDSTC		300	76	54	100
CTR360HDSTC		360	102	54	100
CTR520HDSTC		520	152	54	100
CTR680HDSTC		680	200	54	100
CTR840HDSTC		840	250	54	100
CTR1000HDSTC		1000	302	54	100
CTR360EHDSTC	12.7	360	110	317	100
CTR520EHDSTC		520	161	317	100
CTR620EHDSTC		620	192	317	100
CTR840EHDSTC		840	263	317	100
CTR1000EHDSTC		1000	313	317	100